



Technical features:

- Powered latch-bolt, dead-bolt and extension bolts for automatic operation
- Automatic closing of the door
- Emergency opening with the mechanical key
- Steel case and cover
- Nickel-plated steel dead-bolt
- Non-handed nickel-plated anti-picking latch-bolt
- Anti-crush plates for fixing screws
- Steel extension bolts

Supplied as standard:

- 12V - 2.3 AH lead battery
- Connecting cables

On request:

- Transponder kit
- Connecting cables

Finishes:

- Zinc plated aluminium

Standards:

- Product in compliance with European Draft Standard pr EN 12209:99

Hand:


0 = Non-handed

Cylinder to be ordered separately



CISA e-VOLUTION

Type	Description	DEAD-BOLTS								ITEM			
		No.	Projection	Distance	Throws	Centre Distance	Faceplate	Backset	Unit weight	Pieces	Type	Dim.	Hand



- Deadbolt and latchbolt
- Pre-arranged for additional locking points

4	3,5	25	85	64	3,320	1	1	E6515 25 0
4	3,5	27	85	64	3,320	1	1	E6515 27 0
4	3,5	28	85	64	3,320	1	1	E6515 28 0
3	3,5	32	85	64	3,320	1	1	E6515 32 0
3	3,5	38	85	64	3,320	1	1	E6515 38 0
4	3,5	27	92	64	3,320	1	1	E6615 27 0
4	3,5	28	92	64	3,320	1	1	E6615 28 0
3	3,5	38	92	64	3,320	1	1	E6615 38 0